

Electrical Engineering Department DELHI TECHNOLOGICAL UNIVERSITY

(Formerly Delhi College of Engineering) Shahbad Daulatpur, Bawana Road, Delhi-110042

F. No. DTU/EED/2024/486

Dated: 08.02.2024

NOTICE INVITING QUOTATION

Sealed quotations are invited for the supply of **Data Logger** in Electrical Engineering Department. The sealed quotations on company's letter head including GSTIN No. with **F. No. DTU/EED/2024/486**, should reach to the office of the Head, Department of Electrical Engineering, Delhi Technological University, Main Bawana Road, Shahbad Daulatpur, Delhi-110042 latest by **14/02/2024 by 5PM**.

Item Description	Qty
ioned specification	
tinputs: Thermocouple J, K, T, E, N, R, S and B (IEC-584). Pt100, Pt1000 (IEC-751), 0-20 mA, 4-20 mA, 0- 0-50 mV, 0-60 mV, - 20-20 mV, 0-5 V and 0-10V.	
Thermocouple J, K, T, E and N: 0.2 % of range ± 1 °C. Thermocouple R, S and B: 0.2 % of range ± 3 °C. Pt100, Pt1000, 0-20 mA, 4-20 mA, 0-20 mV, 0-50 mV, 0-60 mV, - 20-20 mV, 0-5 V and 0-10 V: 0.15 % of maximum range.	,
channels that can be individually configured as inputs or	
s SPST-NO/NC, 3 A / 250 Vac	01
used as a Modbus RTU slave or master (can read up to 64	
Mbps.	
DHCP, HTTP, SMTP, SNMP, Modbus RTU, TCP, FTP server and client.	
and officers	
GB.	
C. Relative Humidity (Maximum): 80 % up to 30 °C, peratures above 30 °C, decrease 3 % per °C. Installation II. Pollution degree 2. < 2000 m.	
100 to 240 Vac/dc (50 / 60 Hz) 24 Vdc/ac (50 / 60 Hz)	
(Co. voile)	
e for Windows® XP, Vista and 7. Menus in Portuguese, or English.	
	e for Windows® XP, Vista and 7, Menus in Portuguese, or English.

08.02.24
Department of Electrical Engineering

Copy to:

- 1. Sr. Account Officer
- 2. HOD (CC) to upload on DTU website
- 3. Notice board, EED.